



QX SERIES™ 20V

CORDLESS TORQUE MULTIPLIER

NEXT-GENERATION PRODUCTIVITY

The innovative QX Series™ Cordless Torque Multiplier will reduce your bolting time and cost, while ensuring repeatable accuracy for all torque-critical joints. Designed with a premium Norbar® gearbox and an efficient, time-tested closed-loop transducer, the Torque Multiplier offers proven quality, control and programmable configurations to maximize your productivity.

NOT JUST TORQUE CONTROL BUT **TOTAL CONTROL**

Accuracy:

- Ingersoll Rand's closed-loop transducer control at the heart of the tool delivers precise torque and accurate, traceable results—it's precision where you need it most

Control:

- A multi-function display module allowing for quick setup and real time feedback on every QX Series™ tool
- User-programmable configurations such as torque, angle and gang count that reduce the number of tools needed for multiple applications

Comfort:

- Cordless and compact, the QX Series™ Torque Multiplier allows operators to move freely without the need of bulky air or hydraulic hoses, electrical cords, compressors, generators or powerpacks
- Integrated tethering ring included to safely secure the tools

Communication:

- USB standard, wireless communication optional
- Data management, process control and the ability to adjust tool configurations (Ethernet, fieldbus and I/O capable)

Versatility:

- Fast programming that makes the tool adaptable to multiple applications
- Cordless and portable to allow operators to move freely around any workplace or environment
- HAZ TOOL Class 1 Division 2 option available
- Available in either pistol or angle configurations



ADAPTABLE TO YOUR APPLICATION

From pipeline flange bolts to truck frame assembly, the QX Series™ Cordless Torque Multiplier has the range, accuracy and configurations to tackle your bolting needs. Sharing the same IQ^V Series™ power platform with our industrial cordless and QX Series™ assembly tools, the Torque Multiplier expands our broad range of cordless bolting solutions.



Agriculture & Heavy Equipment



- Chassis & Suspension
- Wheels
- Diesel & Gas Engines
- Tracks

Infrastructure



- Bridges
- Road Ways
- Steel Structures

Oil & Gas



- Flanges
- Heat Exchangers
- High Pressure Valves

Rail



- Rail Car Manufacturing
- Locomotive Assembly
- General Maintenance

Truck & Bus



- Wheels
- Suspension
- Chassis

Wind



- Nacelles
- Gear Boxes
- General Maintenance
- Break-ins

PRECISION ENGINEERED



SUPERIOR COMMUNICATION AND CONTROL

Ingersoll Rand doesn't just give you unprecedented technology, we give you total control of that technology. With up to eight programmable configurations per tool, the QX Series™ Torque Multiplier allows operators to transition seamlessly between different bolting applications. You'll be able to use bolting strategies individually, or combined in one strategy depending on what works best for you.

COMMON BOLTING STRATEGIES

Torque

Achieve desired torque within high and low limits



Angle

Achieve target rotation within high and low limits



Gang Count

Counts all rundowns to ensure all bolts have been fastened



+ If additional control is needed, Ingersoll Rand's INSIGHTqcx Controller or Insight Connect app gives you even more options to adapt to the most complicated bolting applications.

ADVANCED COMMUNICATION OPTIONS FOR PROCESS CONTROL AND REAL-TIME MONITORING



Process Communication Module (PCM) Features

Power Cord	BC10-CORD-US	IC-PCM-2-US	IC-PCM-2-US
Configuration		10 to 1	1 to 1
Tool Connections	Wireless tool connections	10	1
Software	ICS Connect software	•	•
Power Supply	120V AC input, 5V DC output	•	•
Communication	Ethernet to ICS	•	•
Fieldbus Options	Ethernet/IP, DeviceNet, Interbus-S, Profibus, Modbus-TCP		•
Protocols	Open Protocol, Ethernet EOR, Serial EOR		•
Printers/Devices	Serial RS232, bar code, label printing		•
I/O	8 inputs/8 outputs, with behavior assignable through ICS software, operates at 24V DC		•
I/O Power Supply	120V AC input, 24V DC output		•
Indicators	Power ON, System Ready, Wireless Activity, Ethernet Activity	•	•
Ambient Operating Conditions	0-50°C, 20/90% non-condensing humidity	•	•
Enclosure	IP52 mounted in upright vertical position	•	•
System Weight	3.0 lb (1.4 kg)	•	•
Overall Dimensions	11.5 in x 4.1 in x 8.3 in 291 mm x 103 mm x 210 mm	•	•

QX SERIES™ 20V SPECIFICATION

	ft-lbs (Nm)		1 min. rpm	lbs (kg)*	in (mm)*		in (mm)	in	V	Communication
QX Series™ Pistol										
QXC2PT200NPS12	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2PT500NPS12	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2PT1000NPS12	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Via USB Cable Only	
QXC2PT1350NPS16	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Via USB Cable Only	
QXC2PT2000NPS16	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Via USB Cable Only	
QXX2PT200NPS12	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2PT500NPS12	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2PT1000NPS12	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Wireless Enabled	
QXX2PT1350NPS16	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Wireless Enabled	
QXX2PT2000NPS16	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Wireless Enabled	
QX Series™ Pistol Kit										
QXC2P200PS12K2	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2P500PS12K2	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2P1000PS12K2	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Via USB Cable Only	
QXC2P1350PS16K2	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Via USB Cable Only	
QXC2P2000PS16K2	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Via USB Cable Only	
QXX2P200PS12K2	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2P500PS12K2	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2P1000PS12K2	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Wireless Enabled	
QXX2P1350PS16K2	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Wireless Enabled	
QXX2P2000PS16K2	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Wireless Enabled	
QX Series™ Pistol Haz Lock Tool										
QXC2PT200VNPS12	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2PT500VNPS12	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Via USB Cable Only	
QXC2PT1000VNPS12	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Via USB Cable Only	
QXC2PT1350VNPS16	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Via USB Cable Only	
QXC2PT2000VNPS16	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Via USB Cable Only	
QXX2PT200VNPS12	30-148	(40-200)	39	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2PT500VNPS12	74-369	(100-500)	13	8 (3.62)	14.69 (373)	2.20 (56)	3/4"	20V	Wireless Enabled	
QXX2PT1000VNPS16	148-738	(200-1,000)	7	12 (5.44)	16.50 (419)	3.14 (80)	3/4"	20V	Wireless Enabled	
QXX2PT1350VNPS16	200-996	(270-1,350)	5	12 (5.44)	16.50 (419)	3.14 (80)	1"	20V	Wireless Enabled	
QXX2PT2000VNPS16	295-1,475	(400-2,000)	3	15 (6.80)	17.80 (452)	3.14 (80)	1"	20V	Wireless Enabled	
QX Series™ Angle Wrench†										
QXX5A45T0180PS12	27-132	(16-180)	110	11.4 (4.25)	10.40 (264)	3 (76.2)	3/4"	40V	Wireless Enabled	
QXX5A45T0270PS12	40-200	(54-270)	77	11.4 (4.25)	10.40 (264)	3 (76.2)	3/4"	40V	Wireless Enabled	
QXX2A52T0396PS12	59-291	(79-395)	21	9.5 (3.54)	8.50 (216)	3 (76.2)	3/4"	20V	Wireless Enabled	
QXX2A52T0594PS12	88-438	(119-594)	14	10.9 (4.06)	8.50 (216)	3 (76.2)	3/4"	20V	Wireless Enabled	
QXX5A52T0880PS12	130-650	(180-880)	23	12.3 (4.60)	10.40 (264)	3 (76.2)	3/4"	40V	Wireless Enabled	
QXX5A72T1080PS16	160-797	(216-1,080)	19	16 (5.97)	10.40 (264)	3 (76.2)	1"	40V	Wireless Enabled	
QXX5A72T1620PS16	239-1,195	(324-1,620)	13	16 (5.97)	10.40 (264)	3 (76.2)	1"	40V	Wireless Enabled	

*Weight and length do not include battery. Battery sold separately. †Angle wrenches available through IR Solution Centers; angle kits and Haz Loc option coming soon.




QX Series™ Torque Multiplier Kit




Kit includes (1) tool, (2) BL2022 5.0 Ah batteries, (1) BC1121 charger and (1) tool bag. Hard case available as a separate option.

REACTION ARMS

Ingersoll Rand® offers the following variety of reaction arms for different applications. Reaction arms are available in both 52 mm and 72 mm spline drives, depending on the size of the gearbox.



Cranked, 45 or 90 degrees



Straight, aluminum or steel (multiple lengths available)







Plate and pin (multiple lengths available)




Double-sided




Sliding slave kit (multiple lengths available)



Sliding peg and yoke assembly (multiple lengths available)



Sliding yoke, paddle and yoke assembly (multiple lengths available)



Blank welding ring

CUSTOM REACTION ARM OPTIONS

Not all applications are equal — Ingersoll Rand offers custom reaction arms. Please see your certified distributor for more information.

POWER PLATFORM

All QX Series™ 20V tools are compatible with both the 2.5 Ahr and 5.0 Ahr batteries. The 5.0 Ahr is optimum for longer use applications while the 2.5 Ahr is ideal for tighter spaces and reduced weight.

All QX Series™ 40V high torque tools are compatible with the 2.5 Ahr 40V battery.

IQ^{v20} Series™ Battery Charger 20V BC1121



IQ^{v20} Series™ Lithium Ion Battery Pack 20V, 5.0 Ahr BL2022

IQ^{v40} Series™ Battery Charger 40V, 2.5 Ahr BC1161



IQ^{v40} Series™ Lithium Ion Battery Pack 40V, 2.5 Ahr BL4011

ACCESSORIES



Protective Boots



Spring Balancer



Process Communication Module (PCM)



Hard Case



3/4" and 1" Socket Kits



Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.



Learn more at www.ingersollrand.com